

TELEX



AIRMAN 750

THE MOST POPULAR COMMERCIAL AVIATION HEADSET IN THE WORLD

The **Airman 750** is the world's best-selling lightweight headset among professional pilots, air fleet operators and aircraft designers. In fact, the Airman 750 is standard equipment on nearly all commercial airframes.

An amplified noise-canceling electret microphone ensures clear voice transmission.

- A reversible boom enables pilots to adjust the microphone for use on either side of the head.
- Most aircraft manufacturer approved headset
- Cost effective high quality headset
- Ultra-lightweight headset
- Easy to replace windscreen and ear cushions
- Multiple versions available
- 3 years warranty
- FAA TSO approved

FOR MORE THAN 50 YEARS, TELEX INNOVATIONS HAVE PROVIDED PILOTS WITH THE QUALITY COMMUNICATIONS THEY DEPEND ON FOR SAFE, ENJOYABLE FLYING.

It is this long history in aviation, unique understanding of the market, and unmatched combination of capabilities which positions Telex as a supplier to every major airplane manufacturer.

AIRMAN 750

AIRMAN 750
Single sided version



PJ connectors



XLR connector



| MODEL | IMPEDANCE | CONNECTORS | ITEM NO. | SAP NO. |
|---|-----------|-----------------|-----------|---------------|
| AIRMAN 750 Double sided | 150 ff | PJ-068 & PJ-055 | 64300-200 | F.01U.118.067 |
| AIRMAN 750 Double sided | 600 ff | XLR-5-12C | 64300-210 | F.01U.118.069 |
| AIRMAN 750 Double sided | 150 ff | XLR-5-12C | 64300-205 | F.01U.118.068 |
| AIRMAN 750 Double sided, dual Headband, 7' (2.1 m) cord | 150 ff | XLR-5-12C | 64300-208 | F.01U.145.321 |
| AIRMAN 750 Double sided | 600 ff | PJ-068 & PJ-055 | 64300-212 | F.01U.127.249 |
| AIRMAN 750 Double sided, 8' (2.4 m) cord | 150 ff | PJ-068 | 64300-218 | F.01U.145.325 |
| AIRMAN 750 Double sided | 150 ff | XLR-4-11C | 64300-219 | F.01U.118.070 |
| AIRMAN 750 Single sided | 300 ff | PJ-068 & PJ-055 | 64300-300 | F.01U.118.071 |

| ACCESSORIES | ITEM NO. | SAP NO. |
|---|------------|---------------|
| Carrying case | 702126-000 | F.01U.152.568 |
| Ear cushions set for Airman 750 (2 pcs) | 800456005 | F.01U.118.425 |
| Windscreen (1 pcs) for Airman 750 | 800456001 | F.01U.118.421 |
| Windscreen (50 pcs) for Airman 750 | 800456051 | F.01U.393.947 |
| Windscreen (100 pcs) for Airman 750 | 800456101 | F.01U.393.970 |

SPECIFICATIONS

Receivers

- Type: Dynamic
- Impedance: 150 - 600 ff
- Frequency Response: 100 - 3,000 Hz
- Sensitivity: 90 dB SPL/mW @ 1KHz

Gross Weight

- Single sided version: 65 g (2.3 oz)
- Double sided version: 91 g (3.2 oz)

Microphone and Amplifier

- Type: Noise-cancelling electret
- Matching Impedance: 50 - 600 ff
- Frequency Response: 300 - 5,000 Hz
- Sensitivity: -51 +/- 3 dB re: 1 V/ubar
(at 1 kHz, 12 Vdc, 470 ff DC/150 ff AC load)
- Operating Voltage: 8-16 Vdc (TSO load)

Cord length

- 1.7 m - 2.4 m (5.5 ft - 8 ft)

Plug Type

- Microphone: Molded, PJ-068 equivalent
- Receiver: Molded PJ-055 equivalent
- Microphone & Receiver: XLR-5-12C
- Microphone & Receiver: XLR-4-11C

Color

- Black

Certification

- FAA TSO C57a + C58a

North America Global HQ
Bosch Security Systems, LLC
Burnsville, MN
Phone: +1 952 884 4051

Latin America Regional HQ
Robert Bosch Limitada Security Systems
Campinas, SP, Brasil
Phone: +55 19 2103-5995

Europe, Middle East and Africa Regional HQ
Bosch Sicherheitssysteme GmbH (EVI Audio GmbH)
Straubing, Germany
Phone: +49 9421 706-0

Asia-Pacific Regional HQ
Robert Bosch (SEA) Pte Ltd
Singapore
Phone: +65 6571 2528

China Regional HQ
Bosch (Shanghai) Security Systems Ltd.
IBP, Changning District
Shanghai, P.R.China
Phone: +86 400 8310 669