

# THE ALL-IN-ONE THAT WORKS FOR YOU


## IP-3000 SERIES DISPATCH CONSOLES

### USER FRIENDLY



Combines console, software and direct IP interfaces into single easy-to-configure devices, with flexible layout options and an enhanced GUI

### SIMPLIFIED MANAGEMENT



Makes system administration, configuration and software updates quick and easy, whether on-site or remote

### BRIDGING SYSTEMS



Interconnect with a variety of systems seamlessly using industry standards and APIs



# ADVANCED HARDWARE AND SOFTWARE FOR THE ULTIMATE “ALL-IN-ONE” UX

Two form factors are available: the **IP-3008** (eight lines) and **IP-3018** (18 lines). Each is available in public safety, enterprise or standard configurations to suit the specific requirements of different dispatch verticals. Public safety and enterprise configurations are equipped with direct IP interfaces for interoperability with digital radio equipment, e.g. NEXEDGE®. Public safety-configured devices also offer encryption and compliance with the P25 suite of system standards. Standard configuration models connect to an external IP-224, making them a cost-effective choice for integration with existing Telex systems, and may be upgraded to public safety and enterprise configurations as needed. A two-channel **IP-3002** model is also available in standard configuration (non-upgradeable), in the same form factor as the IP-3008.

The IP-3000 series will offer packet encryption, monitoring, user permissions, verification and third-party VPN for secure remote use. As well as being compatible with legacy Telex hardware, the series is interoperable with a wide range of industry technologies - including IPv6, upcoming Push-to-Talk over Cellular (PoC), SIP telephony, radio protocols, security enhancements and more. APIs enable seamless integration with other types of systems.

Smooth hands-on functionality is ensured via the IP-3000's best-in-class feature lineup. High-resolution TFT LCD 15:9 widescreen video displays (7" & 15.6"), reliable and responsive touchscreens, and high-quality speakers deliver an excellent audio-visual performance in any lighting conditions or working environment. Each console is equipped with USB ports and an output for an external monitor. The units are easy to mount and positioning can be further adjusted using the optional adjustable incline mechanism. User I/Os include a handset with DTMF pad, a gooseneck microphone with illuminated PTT key, and six (IP-3002/IP-3008) or 16 (IP-3018) programmable and color-coded hot keys. Additional programmable keypads are available as options. The consoles come with a choice of handset or gooseneck microphone; headsets may also be used via an ADHB-4 (Advanced Digital Headset Box).

New versions of C-Soft and Telex System Manager (TSM) offer enhanced layout design, GUI personalization and system management - all geared towards supporting simple menus and more streamlined workflows.

	IP-3002 IP-3008	IP-3018
<b>Processor</b>	Intel N3350	Intel J1900
<b>Memory</b>	32 GB SSD 8 GB RAM	256 GB SSD 8 GB RAM
<b>Controls</b>	<ul style="list-style-type: none"> <li>Handset with DTMF pad</li> <li>Goose-Neck Microphone with illuminated PTT key</li> <li>6 Programmable keys</li> </ul>	<ul style="list-style-type: none"> <li>Handset with DTMF pad</li> <li>Goose-Neck Microphone with illuminated PTT key</li> <li>16 Programmable keys</li> </ul>
<b>Connectors</b>	<ul style="list-style-type: none"> <li>1x 12V in</li> <li>1x handset</li> <li>1x LAN</li> <li>1x HDMI</li> <li>2x USB</li> </ul>	<ul style="list-style-type: none"> <li>6x USB</li> <li>2x LAN</li> <li>1x 12V in</li> <li>1x digital in</li> <li>1x VGA</li> <li>1x 3.5 mm mic out</li> <li>1x 3.5 mm audio in</li> <li>1x 3.5 mm mic in</li> <li>1x 3.5 mm line in</li> <li>1x 3.5 mm line out</li> </ul>
<b>Screen</b>	<ul style="list-style-type: none"> <li>7 in TFT LCD touchscreen</li> <li>Accutouch 5-wire resistive by ELO</li> <li>15:9 widescreen</li> </ul>	<ul style="list-style-type: none"> <li>15.6 in TFT LCD touchscreen</li> <li>Accutouch 5-wire resistive by ELO</li> <li>15:9 widescreen</li> </ul>
<b>Dimensions</b> <i>W x D x H (mm)</i>	332 x 278 x 113	510 x 342 x 112
<b>Operating System</b>	Windows 10 Enterprise LTSC	
<b>Pre-loaded software</b>	Console applications	
<b>VU Meter</b>	Three-color bar graph	
<b>Speakers</b>	Selected and Unselected (2x 2W)	
<b>Power</b>	External inline 110/220 VAC. UL and Energy Level VI	
<b>Cooling</b>	Fan less	
<b>Mounting options</b>	VESA Mount pattern or desktop with adjustable incline option	
<b>Certifications</b>	UL, CE and FCC for Emission	