

## Network Recorder NR-V2



<b>Power Requirements</b>	100-240 VAC 50/60Hz 7A
<b>Power Supply</b>	Antec Earth Watts EA 430 430W ATX 12V Power Supply
<b>Operating System</b>	MS Windows XP Pro SP2 OEM
<b>Recovery Software</b>	Acronis True Image OEM
<b>USB Port</b>	Back: Eight (8) ports Front: Two (2) ports
<b>Drive Bays</b>	External: 3" x 3.5" and 2" x 3.5" Internal: 1" x 3"
<b>Hard Disk Drive – Data</b>	Seagate ST3500320AS. 500GB, SATA2, 7200rpm, in Raid 1 (mirror) Configuration on Raid controller card. Two (2)
<b>Hard Disk Drive – OS Base</b>	Seagate ST3250410AS, 250GB, SATA, 7200rpm, 16MB NCQ. One (1)
<b>Removable Drive Kit</b>	Seagate ST3250410AS, 250GB, SATA2, 7200rpm, 16MB NCQ HDD installed onto ICY Dock. One (1)
<b>Controller</b>	Adaptec 1220SA, SATA 2 RAID, 2-Port, PCI-Express for Hard Disk Drive—Data Array
<b>Port</b>	One (1): Integrated RS232, One (1): IEEE1394a, One (1) Parallel, One (1) PCR Express x16 slot, One (1) PCI Exeperess xl slot, Two (2) PCI 2.2 slots.
<b>Motherboard</b>	Intel DQ35JO Core 2/Quad, Intel Q35 Chipset, FSB 1333/1066/800, Intel vPro Ready, Audio , Viedeo and Gigabit Ethernet Micro-ATX
<b>SDRAM</b>	4 GB 667MHzDDR2
<b>CD Burner</b>	Samsung DVDRW with CDBurner XO and Nero OEM installed.
<b>Integrated Graphics Media Accelerator</b>	Intel X3100
<b>Integrated Gigabit Ethernet Controller</b>	Intel 82566DM
<b>Sound Card</b>	Creative Labs SB Audiology 7.1 SB0610VP
<b>Keyboard and Mouse</b>	US English keytronics Lifetime Classic II and Logitech LX3 Optical
<b>Operating Temperature</b>	
<b>Dimensions</b>	7" H x 19" W x 17.7" D (with rounded handles) 4RU Rack Mount
<b>Weight</b>	

This specification information is preliminary and is subject to change without notification.