

Specifications

Innovating the Future of Global Communications

Dispatch PC



- Custom Slim Mini-ITX Case with 2x2.5" HOD mount points (Internal DC-DC ATX PSU) (Black) [230 (W) x 215 (0) x 65 (H)mm;
 9.05"(W) x 8.46"(D) x 2.55"(H) Vesa mount kit available
- · Power Adapter for AC-DC, 110AC/12V 90W, PSE Mark Compliant
- Mini-ITX Long LifeCycle motherboard based on the Intel Q77 chipset (20–2016), Socket 1155 (3rd Gen), FSB 1333/1066, 2xDDR3 max 16GB, Intel graphics controller with 1x HDMI, 1x VGA and 1 x OVI-D, Dual Intel Pro gigabit Ethernet, 2x SATA3 ports supporting RAID 0, 1 and 4x SATA2 ports supporting Intel RAID 0, 1, 5, 10, Realtek ALC662 5.1 audio, 1x PCI-Express 3.0 x 16, 2x serial ports
- Intel Core i3 2.8GHz Processor with 3MB cache, LGA-1155, 35W (low thermal impact CPU)
- 8GB DDR3-1333 SODIMM RAM installed (2 sticks x 4GB = 8GB, Max of 16GB)
- Segate 250GB 5400rpm SATA2 16MB cache notebook hard drive (Active <2W, 2.5 inch)
- Booting from the installed Intel Solid State Drive (SSD), 60GB or larger, SATA3, maximum read transfer rate: 500MBps, maximum write transfer rate: 400MBps (Active <1W, 2.5 inch, MTBF=>1,200,000 hours)
- · Microsoft Windows 7 Professional SP1, 64-bit OEM (Current Telex Radio Dispatch Image installed and tested)
- US English Keytronics Lifetime Classic II Keyboard USB (black) with lifetime manufacture warranty and Logitech USB optical mouse (black/charcoal)
- · Wall Mounting Bracket (removable with bracket mounting instructions)
- · Includes FCC's Declaration, RoHS, and CE Declaration of Conformance
- · Rubber mounting feet for case, included in media/documentation bag
- 3-years parts and labor depot warranty